

# Safety Light Curtain Type 4

## Hand Protection


# SG4-30IE090C1

Part Number



- Completely integrated electronics
- Fix blanking, floating blanking and reduced resolution, cascading, muting
- Serial interface

These safety light curtains are distinguished by their compact design. They are also equipped with numerous auxiliary functions, allowing for adaptation to the respective application in a highly individualized fashion. The adequate mounting angle BEF-SET-33 is included in the delivery.



## Technical Data

### Optical Data

Range	0,5...20 m
Safety Field Height (SFH)	930 mm
Resolution	30 mm
Light Source	Red Light
Opening Angle	± 2,5 °

### Electrical Data

Sensor Type	Receiver
Supply Voltage	24 V DC
Current Consumption (U <sub>b</sub> = 24 V)	300 mA
Response Time	14 ms
Temperature Range	-20...50 °C
Storage temperature	-25...70 °C
No. Safety Outputs (OSSDs)	2
Safety Output Voltage Drop	< 2,5 V
PNP Safety Output/Switching Current	300 mA
Signal Outputs	1
Signal Output Voltage Drop	< 2,5 V
Signal Output/Switching Current	200 mA
Short Circuit and Overload Protection	yes
Reverse Polarity Protection	yes
Interface	RS-485
Protection Class	III

### Mechanical Data

Housing Material	Aluminum
Disk Material	Polycarbonate
Degree of Protection	IP67
Connection	M12 × 1; 8-pin

### Safety-relevant Data

ESPE Type (EN 61496)	4
Safety Category (EN ISO 13849-1)	4
Performance Level (EN ISO 13849-1)	PL e
PFHD	3,08 × E-8 1/h
Service Life TM (EN ISO 13849-1)	20 a

### Function

Hand Protection	yes
Restart Inhibit	yes
Contactors Monitoring	yes
Cascading	yes
Fix Blanking	yes
Floating Blanking	yes
Reduced Resolution	yes
Serial Communication	yes


Connection Table No.	28
Control Panel No.	S4
Suitable Connection Technology No.	88   88s
Suitable Mounting Technology No.	700
Suitable Serial Interface Plug No.	11

## Suitable Emitter


SG4-30IS090C1

## Complementary Products

Deflection Mirror Z2UG003
Laser Alignment Aid SZ0-LAH1
Muting Indicator SM0-00CA000C1
Protection Column with Deflection Mirror SZ000EU125NN01
Protection Column with Screening Grid SZ000EG125NN01
Safety Relay SG4-00VA000R2, SR4B3B01S, SR4D3B01S
Sistema Library software DNNF007
Software wsafe DNNF006



### Ctrl. Panel



- 03 = Error Indicator
- 20 = Enter Button
- 52 = OSSD ON
- 53 = OSSD OFF
- 55 = Blanking
- 56 = Dip-Switch
- 60 = Display

