

## 1-120 Cylinder Quarter-Turn Pr20.1 L18



for cutout 20.1, length 18

### Advantages

- Cylinder Quarter-turn.
- RH or LH application.
- The Quarter-turn consists of two basic components which can be combined to suit your application.
- On request parts can be assembled by DIRAK.
- A pre-assembled Quarter-turn can be installed in the cutout.
- All locks supplied with two keys.
- **Water- and dust-tight according to IP65 DIN EN 60529 by:** Dust cap 200-4101.
- **Water- and dust-tight according to IP65/IP67 by:** Dust cap 200-4103.

### Materials

- a)
  - **Housing:** zinc die, chrome plated or black
- b)
  - **Cam:** steel, zinc plated or PA black
- c)
  - **Dust caps:** PP, black or TPU, black
- d)
  - **Finger pull:** PA, black



## Quarter-turn with cylinder, zinc die, chrome plated

a) 200-9201.00-00000 Diameter Ø28 Grounding nut 18,0 mm screw-on max. 8,0 mm

### \* Complementary products

- e) 1-270 **Dust caps and Sealing Plug Pr20.1**
- c) 1-270.01 **Finger Pull for Quarter-Turn Pr20.1**
- b) 1-102 **Cams L35/45**
- b) 1-262 **Cam with Ramp**
- b1) 1-095 **Cams PA**

### 🔧 Assembly options

200-0001.00-00000 **Assembling cam without o-ring**



