


AS-Interface CompactLine module

CompactModule 4DI M12



Made in Germany

Electrical data

Operating voltage	[V]	26.5...31.6 DC; ("supply class 2" to cULus)
Max. current consumption from AS-i	[mA]	250
Inputs		
Number of digital inputs		4
Input circuit of digital inputs		PNP
Max. total current rating of inputs	[mA]	200
Input current limitation	[mA]	15
Input current High	[mA]	6...10
Input current Low	[mA]	0...2
Min. switching level high signal	[V]	11
Digital inputs protected against short circuits		yes
Sensor supply of the inputs		AS-i

AC2410



AS-Interface CompactLine module

CompactModule 4DI M12

Operating conditions				
Ambient temperature	[°C]		-25...80	
Protection		IP 67; ("enclosure type 1" according to cULUS; when flat cables are used E7400x / E7401x)		
Tests / approvals				
EMC		EN 50295		
AS-i classification				
AS-i version		2.11 + 3.0		
AS-i addressing		IR addressing possible		
Extended addressing mode possible		no		
AS-i profile		S-0.0.E		
AS-i I/O configuration	[hex]	0		
AS-i ID code	[hex]	0.E		
AS-i certificate		40501		
Assignment of the data bits	data bit	D0	D1	D2
	input	1	2	3
	socket	I-1	I-2	I-3
	pin	2+4	2+4	2+4
Mechanical data				
Weight	[g]	291.6		
Type of mounting		AS-i flat cables directly connectable		
Materials		PA; socket: brass nickel-plated; threaded inserts in the lower part: brass nickel-plated; O-ring: FKM; piercing contacts: CuSn6 nickel-plated and tin-plated;		
Displays / operating elements				
Display	operation		LED, green	
	errors		LED, red	
	function		LED, yellow	
Accessories				
Accessories (optional)		Stainless steel sleeve, for installation in case of high mechanical stress , E70402		
Remarks				
Remarks	Do not connect any of the following points to an external potential:			
	I-, I+, I1, I2, I3, I4			
	The connections are electrically connected with the AS-i cable.			
Pack quantity		1 pcs.		
Electrical connection				
Inputs				
1	Sensor supply L+			
2+4	data input 1 internally bridged			
3	Sensor supply L-			
5	functional earth			
Connector: M12				

AC2410



AS-Interface CompactLine module

CompactModule 4DI M12

