Elastomeric Coupling Catalog

Download the most up-to-date versions at www.rexnord.com






Omega Elastomeric Couplings (Inch)



Omega Close-Coupled Design with Straight Bore Hubs



(HUBS OUTBOARD)

(HUBS INBOARD)

| Coupling Size | Recom. Max. Bore (in) ① | Continuous HP/100 RPM | Continuous Torque (lb-in) | Max. RPM | Dimensions (in) | | | | | | | |
|------------------|----------------------------------|-----------------------------|---------------------------------|-------------|-----------------|------|------|-------|-------|-------|-------|---------------|
| | | | | | A | В | С | | D | F | | Weight ② (lb) |
| | | | | | | | (In) | (Out) | | (in) | (Out) | |
| E2 | 1.13 | 0.30 | 190 | 6600 | 3.50 | 0.94 | 1.34 | 1.90 | 1.85 | 3.22 | 3.78 | 1.2 |
| E3 | 1.38 | 0.58 | 365 | 6600 | 4.00 | 1.50 | 0.81 | 1.31 | 2.32 | 3.81 | 4.31 | 2.4 |
| E4 | 1.63 | 0.88 | 550 | 6600 | 4.56 | 1.69 | 0.44 | 1.31 | 2.60 | 3.81 | 4.69 | 3.0 |
| E5 | 1.88 | 1.48 | 925 | 6600 | 5.38 | 1.75 | 0.81 | 1.81 | 3.13 | 4.31 | 5.31 | 5.4 |
| E10 | 2.13 | 2.30 | 1450 | 6600 | 6.38 | 1.88 | 0.56 | 1.84 | 3.65 | 4.31 | 5.56 | 8.2 |
| E15 | 2.13 | 2.86 | 1800 | 6600 | 6.38 | 1.88 | 0.56 | 1.84 | 3.65 | 4.31 | 5.56 | 8.3 |
| E20 | 2.38 | 3.65 | 2300 | 6600 | 7.25 | 2.06 | 0.50 | 2.38 | 4.48 | 4.62 | 6.50 | 13.0 |
| E30 | 2.88 | 5.79 | 3650 | 5800 | 8.25 | 2.31 | 0.56 | 2.44 | 5.42 | 5.19 | 7.06 | 21 |
| E40 | 3.38 | 8.85 | 5500 | 5000 | 9.50 | 2.50 | 0.56 | 2.68 | 6.63 | 5.56 | 7.68 | 35 |
| E50 | 3.63 | 12.14 | 7650 | 4200 | 11.00 | 2.75 | 0.63 | 3.38 | 8.13 | 6.13 | 8.88 | 54 |
| E60 | 4 | 19.84 | 12,500 | 3800 | 12.50 | 3.25 | 0.69 | 3.44 | 8.75 | 7.19 | 9.94 | 72 |
| (E70) | 4.5 | 35.12 | 22,125 | 3600 | 14.00 | 3.62 | 0.75 | 3.75 | 9.25 | 8.00 | 11.00 | 86 |
| E80 | 6 | 62.7 | 39,500 | 2000 | 16.00 | 4.87 | 0.75 | 5.00 | 11.25 | 10.50 | 14.75 | 170 |
| E100 | 6.75 | 135 | 85,050 | 1900 | 21.00 | 5.50 | 1.75 | 3.75 | 14.13 | 12.75 | 14.75 | 244 |
| E120 | 7.5 | 270 | 170,100 | 1800 | 25.00 | 6.00 | 2.25 | 4.88 | 17.63 | 14.24 | 16.88 | 425 |
| E140 | 9.00 | 540 | 340.200 | 1500 | 30.00 | 7.00 | 3.00 | 5.00 | 20.88 | 17.00 | 19.00 | 746 |

- ① See page 17 for larger bore capacities with shallow keyways.
- ② With maximum bore hubs.

Split-in-Half Flex Element

Allows disassembly and replacement without disturbing hubs or connected equipment.



Straight Bore Hubs

Reversible Hubs

Accommodates different shaft spacing requirements, and allows compression bushings to be installed from either side of the hub.



QD Hubs and Bushings



Taper-Lock Hubs and Bushings



866-REXNORD/866-739-6673 (Within the US) 414-643-2366 (Outside the US) www.rexnord.com

Why Choose Rexnord?

When it comes to providing highly engineered products that improve productivity and efficiency for industrial applications worldwide, Rexnord is the most reliable in the industry. Commitment to customer satisfaction and superior value extend across every business function.

Delivering Lowest Total Cost of Ownership

The highest quality products are designed to help prevent equipment downtime and increase productivity and dependable operation.

Valuable Expertise

An extensive product offering is accompanied by global sales specialists, customer service and maintenance support teams, available anytime.

Solutions to Enhance Ease of Doing Business

Commitment to operational excellence ensures the right products at the right place at the right time.

REXNORD

Rexnord Company Overview

Rexnord is a growth-oriented, multi-platform industrial company with leading market shares and highly trusted brands that serve a diverse array of global end markets.

Process and Motion Control

The Rexnord Process & Motion Control platform designs, manufactures, markets and services specified, highly engineered mechanical components used within complex systems where our customers' reliability requirements and the cost of failure or downtime are extremely high.

Water Management

The Rexnord Water Management platform designs, procures, manufactures and markets products that provide and enhance water quality, safety, flow control and conservation.