



NOTE: PRELIMINARY SPECIFICATIONS

SPECIFICATIONS	
CABLE DATA	
CABLE LENGTH	10 METERS
INDIVIDUAL LEADS	10x18 AWG
JACKET COLOR/MATERIAL	BLACK/OIL RESISTANT PVC
MATERIAL	
HOUSING MATERIAL/COLOR	PA 6 GF 30 (NYLON)/YELLOW
CONTACT CARRIERS	PUR (POLYURETHANE)
CONTACTS	GOLD PLATED
SEALING	NBR GASKET
ELECTRICAL DATA	
OPERATING VOLTAGE	250 V
MECHANICAL DATA	
PROTECTION CLASS to DIN 40050	IP 67 ONLY WHEN ALL RECEPTICLES ARE COVERED WITH PLUGS OR CONNECTED
OPERATING TEMPERATURE	-40°C to 90°C (-40°F to 194°F)

PIN-OUT		GROUND = GN	(L2) LOAD: #4 = BU
2=(L2)LOAD		(L1) COMMON = WH	(L2) LOAD: #5 = GY
3=(L1)COMMON		(L2)LOAD #1 = RD	(L2) LOAD: #6 = YE
1=GROUND		(L2)LOAD #2 = VT	(L2) LOAD: #7 = DG
		(L2)LOAD #3 = BK	(L2) LOAD: #8 = BN
MATERIAL PA 6 GF 30 PLASTIC HOUSING		TURCK INC 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 PHONE: (763) 553-7300	
DRFT	CBM	DATE 9/10/97	PART NO./DESCR.
DSGN		Y#	VBKB 80-10
DIMENSION UNITS: INCHES [MILLIMETERS]		SIZE B	REV P1
		SCALE N/A	SHEET 1 OF 1

P1		CBM	9/10/97	
REV	DESCRIPTION	DRFT	DATE	ECO NO.
REVISIONS				