



Technical Characteristics

Catalog Reference Number	9050CT9601
Ampere Rating	10A
Approvals	UL Listed File Number E78351 CCN NLDX - CSA Certified File Number LR60905 Class 321104 - CE Marked
Maximum Voltage Rating	240VAC
Horsepower Rating	1/3HP@120VAC - 1/2HP@240VAC
Type	JCK
Type of Pins	Tubular
Timing Mode	On Delay, Off Delay, Interval, One Shot, Repeat Cycle
Timing Range	0.05 - 9.99 Seconds; 0.1 - 99.9 Seconds; 1 - 999 Seconds; 0.1 - 99.9 Minutes; 1 - 999 Minutes
Contact Break	3A@120VAC, 1.5A@240VAC
Mounting Type	Socket
Number of Pins	11 Pin
Contact Configuration	2 N.O./2 N.C.
Contact Arrangement	DPDT
Contact Make	30A@120VAC, 15A@240VAC
Features	Up to +/- 0.1 Percentage Repeat Accuracy; Transient Protected; Variable or Fixed Time Delay; Available in 5 timing modes.
Coil Voltage	120VAC@50/60Hz

Shipping and Ordering

Category	21652 - Timers, Plug-In, Type JCK60 & JCK70
Discount Schedule	CP2
Article Number	785901053880
Package Quantity	1
Weight	0.28 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.