

# PNEUMATIC IMPACT WRENCH

Reliable, powerful impact wrench with fast torque build-up.



**DSS 3/4" H**  
Art. No. 0703 773 0

**Recommended maximum bolt size: M27.**

**Ideal for changing tires on utility vehicles.**

**Well-balanced device in rugged aluminum housing.**

Long service life and optimum distribution of center of gravity.

**Rubber-coated and ergonomically shaped handle.**

**User-friendly right/left rotation switching and adjustable trigger.**

The handle does not become cool during work.

The device is very handy and user-friendly.

**High-quality pin impact mechanism in oil tank with six-vane motor.**

Increased service life thanks to constant lubrication.

Nearly vibration-free.

**3-year warranty.**

On manufacturing and material defects.

Technical data												
Type	Square drive	Operating torque* in Nm	Max. releasing torque in Nm	Avg. operating pressure in bar	Weight in kg	Dimensions (L x W x H) in mm	Avg. air consumption in L/min.	Connection thread in inches	Minimum hose dia. in mm	Sound pressure level in dB(A)	Art. No.	P. Qty.
DSS 3/4" H	3/4"	350 - 1,440	1,500	6.3	4.73	261 x 87 x 227	215	3/8"	11	96	<b>0703 773 0</b>	1

\* The working torque is the torque usually reached under average working conditions. It is dependent on the highly variable ambient conditions (air pressure, hose diameter, soiling etc.).



The reversing piston and the four tightening torque stages can be operated with one hand and enable optimum adaptation to the task at hand.



Through-hole for locking pin in 3/4" square.



Ergonomic, rubber-coated handle and 360°-rotatable air intake.

Available in the fleet management system **ORSY®fleet**.

Accessories		
Designation	Art. No.	P. Qty.
Plug-In Nipple with R 3/8" male thread made of nickel-plated steel	<b>0699 100 638</b>	3
Small Mist Oiler with 3/8" female thread	<b>0699 070 338</b>	1
Special Oil for pneumatic tools (1 L)	<b>0893 050 5</b>	
3/4" Power Socket Wrench Sets	<b>0714 14...</b>	

Stage	Tightening torque in Nm, approx.
1	350
2	685
3	1,300
4	1,440

When used regularly, the machine should be lightly oiled via the compressed-air supply every day. The use of a mist oiler is recommended.