


Combination C08


= "Most Popular"



C08-02-FKG0

Features

- Components Integrated into Single Unit
- Modern Design and Appearance
- Light Weight, Ready-to-Mount Assembly Comes Standard with Flush-Mount Pressure Gauge and Modular T-bracket / Joiner Assembly
- High Flow Capacity
- Quick-Disconnect Bowl / Bowl Guard



Dimensions

Models	Inches (mm)	A	B	B ₁	C	D	E	E	F	G	H	J	J ₁
Standard Unit C08-XX-FKG0		4.72 (120)	3.75 (95)	—	2.25 (57)	1.47 (37)	6.00 (152)	—	1.61 (41)	3.15 (80)	1.37 (35)	1.57 (40)	1.57 (40)
Piston Drain C08-XX-FRG0		4.72 (120)	—	3.53 (90)	2.25 (57)	1.47 (37)	—	5.78 (147)	1.61 (41)	3.15 (80)	1.37 (35)	1.57 (40)	1.57 (40)

Specifications

Flow Capacity*	1/8	29 SCFM (13.7 dm ³ /s)
	1/4	44 SCFM (20.8 dm ³ /s)
Gauge Port** (2)	NPT	1/8
Maximum Supply Pressure	Plastic Bowl	150 PSIG (10.3 bar)
	Metal Bowl	250 PSIG (17.2 bar)
Operating Temperature	Plastic Bowl	14° to 125°F (-10° to 52°C)
	Metal Bowl	14° to 150°F (-10° to 65.5°C)
Port Size	NPT / BSPP-G	1/8, 1/4
Standard Filtration	5 Micron	
Weight	1.96 lb. (0.9 kg)	

* Inlet pressure 100 PSIG (6.9 bar). Secondary pressure 90 PSIG (6.2 bar).

** Non-gauge option only.

"F" Series Filters, Type "A" 5 micron elements: All Wilkerson Type "A" 5 micron elements meet or exceed ISO Class 3 for maximum particle size and concentration of solid contaminants.

Materials of Construction

Body	Zinc	
Bonnet	PBT	
Bowl	Plastic Bowl	Polycarbonate
	Metal Bowl	Zinc
Bowl Guard	Nylon	
Diaphragm Assembly	Brass / Nitrile	
Filter Element	Polyethylene	
Knob	Acetal	
Seals	Plastic Bowl	Nitrile
	Metal Bowl	Nitrile
Sight Dome	Polycarbonate	
Springs	Steel	
Suggested Lubricant	Airline Oil F442001	
Valve	Brass / Nitrile	

 = "Most Popular"

Note: For Kits and Repair Parts, see individual pages for Filters, Regulators, and Lubricators.

 WARNING
<p>Product rupture can cause serious injury. Do not connect regulator to bottled gas. Do not exceed maximum primary pressure rating.</p>

CAUTION:

REGULATOR PRESSURE ADJUSTMENT – The working range of knob adjustment is designed to permit outlet pressures within their full range. Pressure adjustment beyond this range is also possible because the knob is not a limiting device. This is a common characteristic of most industrial regulators, and limiting devices may be obtained only by special design.

For best performance, regulated pressure should always be set by increasing the pressure up to the desired setting.

B
Filters, Regulators, Lubricators

Ordering Information

Model Type	Port Size	Plastic Bowl / Bowl Guard / Without Gauge 0 to 125 PSI (0 to 8.6 bar)	Plastic Bowl / Bowl Guard / With Gauge 0 to 125 PSI (0 to 8.6 bar)	Metal Bowl / Without Gauge 0 to 125 PSI (0 to 8.6 bar)	Metal Bowl / With Gauge 0 to 125 PSI (0 to 8.6 bar)
Manual Drain	1/8	C08-01-FK00	C08-01-FKG0	C08-01-FL00	C08-01-FLG0
	1/4	C08-02-FK00	C08-02-FKG0	C08-02-FL00	C08-02-FLG0
Piston Drain	1/8	C08-01-FR00	C08-01-FRG0	C08-01-FS00	C08-01-FSG0
	1/4	C08-02-FR00	C08-02-FRG0	C08-02-FS00	C08-02-FSG0

Options - To order an option supplied with the unit model, add the appropriate coded suffix letter in the designated position of the model number.