

834102400000

Modular timer 8 - 12 - 16 A










This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:

Modular timers, Mono-function, 1 CO (SPDT), 16 A, AC/DC coil, 240 V, operating from 16.8 to 265 V (AC)/(DC), rated power 1.5 VA (AC) / 2 W (DC), Version: Standard, ambient temperature from -20 to +60 °C

[BROWSE PRODUCT PAGE](#)

Technical Features:

Commercial Description:	Modular timer, 22.5mm wide, multi-voltage and single BE function (Off-delay with control signal). Features include: - Eight time scales from 0.05 s to 10 days - High input/output insulation - Wide power supply range (24... 240) V AC/DC - “Blade + cross”: Both flat blade and cross-head screwdrivers can be used to adjust the range and function selectors, the timing trimmer, and to disengage the 35 mm rail clip - Multi-voltage versions with “PWM clever” technology - Compliant with EN 45545-2: 2013 (fire and smoke protection), EN 61373 (impact and vibration resistance, category 1, class B), EN 50155 (resistance to temperature and humidity, class T1).
Contact configuration:	1 CO (SPDT)
Delay setting:	(0.05...1)s, (0.5...10)s, (0.05...1)min, (0.5...10)min, (0.05...1)h, (0.5...10)h, (0.05...1)d, (0.5...10)d
Dimensions:	22.5x78.8x96 mm
Functions:	Mono-function
Nominal voltage:	240 V
Operating range AC:	16.8...265 V
Operating range DC:	16.8...265 V
Rated contact voltage:	250 V AC
Rated current (contacts):	16
Certifications and quality approvals (according to type):	      

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form the basis of a contract.

Need more information?
[Contact our sales](#) [Find a dealer](#)