

PVC plates

Suitable for external panel, adhesive and non adhesive. High quality and long lasting resistance.



ADHESIVE

mm		WHITE	YELLOW	METAL	LABELPHOS	ORANGE	RED
40 x 40	132	EVO44040W	EVO44040Y	EVO44040M	EVO44040PH	EVO44040O	EVO44040R
70 x 30	33	EVO43070W	EVO43070Y	EVO43070M	EVO43070PH	EVO43070O	EVO43070R
90 x 40	22	EVO44090W	EVO44090Y	EVO44090M	EVO44090PH	EVO44090O	EVO44090R
100 x 60	22	EVO460100W	EVO460100Y	EVO460100M	EVO460100PH	EVO460100O	EVO460100R
145 x 60	15	EVO460145W	EVO460145Y	EVO460145M	EVO460145PH	EVO460145O	EVO460145R
150 x 60	15	EVO460150W	EVO460150Y	EVO460150M	EVO460150PH	EVO460150O	EVO460150R
500 x 80	14	EVO480500W	EVO480500Y	EVO480500M	EVO480500PH	EVO480500O	EVO480500R
AVAILABLE COLOURS		MATERIALS		THICKNESS		TEMPERATURE RANGE	

NON ADHESIVE

mm	Ø HOLE mm	PROTECTIVE SLIDES COMPATIBILITY		WHITE	YELLOW	METAL	LABELPHOS	ORANGE	RED
70 x 30	3,2	SIT0V301	33	EVO3070W	EVO3070Y	EVO3070M	EVO3070PH	EVO3070O	EVO3070R
90 x 40	3,2	SIT0V401	22	EVO4090W	EVO4090Y	EVO4090M	EVO4090PH	EVO4090O	EVO4090R
100 X 60	3,2	SIT0V601	22	EVO60100W	EVO60100Y	EVO60100M	EVO60100PH	EVO60100O	EVO60100R
150 X 60	3,2	-	15	EVO60150W	EVO60150Y	EVO60150M	EVO60150PH	EVO60150O	EVO60150R
AVAILABLE COLOURS		MATERIALS		THICKNESS		TEMPERATURE RANGE		CERTIFICATIONS	

Industrial automation

Industrial plant

Industrial wiring

Civil system

DITTA COSTRUTTRICE:
Grafoplast
15077 Predosa (AL) ITALY
Tel. 0131.718477-Fax 0131.718585
www.grafoplast.it

DESCRIZIONE QUADRO:
GRAFOPLAST

NORM. _____

ANS _____

TENSIONE NOMINALE _____ V lcc _____ kA

TENS. NOM. ISOLAMENTO _____ V Frequenza _____ Hz

CORRENTE NOMINALE _____ A FASI _____ 3P+N+T

CE

IP

RIF. COMMESSA _____

N° MATRICOLA _____

DATA COSTRUZIONE _____