

ELECTRON ST



To the product



Technical data

Article	145.562; 145.563; 145.564; 145.565; 145.566; 145.567; 145.568; 145.574; 146.370; 149.673; 154.839	
Voltage	120 V; 200 V; 220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	2300-3400 W	
Temperature	40-650 °C	104-1202 °F
Temperature setting stepless	Yes	
Airflow (20°C)	360 l/min	12.71 cfm
Stepless air volume adjustment	No	
Static pressure	3400 Pa	0.49 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	50 mm / 2 in	
Length	338 mm	13.3 in
Device diameter	90 mm	3.54 in
Handle diameter	56 mm	2.2 in
Weight	1.18 kg	2.6 lb
Power cable length	3 m	9.84 ft



ELECTRON ST

Technical data

Plug	AU, 3 poles, 15A; CEE blue, 3 poles, 16A; CEE yellow, 3 poles, 32A; CH T23 (IP55), 3 poles, 16A; CN, 3 poles, 16A; EU, 2 poles, 16A; JP, 3 poles, 20A; KR, 2 poles, 16A; US, 3 poles, 20A; without plug
Noise emission level	67 dB (A)
Approvals	CE; KC; S+
Protection class	II
Approval number	MSIP-REM-Le1-ElectronST
Country of origin	CH

Scope of delivery

Tool case

Product items

145.562	ELECTRON ST, 120V/2400W, US plug
145.563	ELECTRON ST, 120V/2400W, CEE 3/32
145.564	ELECTRON ST, 200V/3000W, JP plug
145.565	ELECTRON ST, 230V/3400W, AU plug
145.566	ELECTRON ST, 230V/3400W, CN plug
145.567	ELECTRON ST, 230V/3400W, EU plug
145.568	ELECTRON ST, 230V/3400W, CEE 3/16
145.574	ELECTRON ST, 230V/3400W, w/o plug
146.370	ELECTRON ST, 230V/3400W, CH plug
149.673	ELECTRON ST, 230V/2300W, EU plug
154.839	ELECTRON ST, 220V/3400W, KR plug