

Main Features

- Heavy duty stainless steel construction
- Magnetically shielded
- Radial exit
- Captive guided extension
- Mild steel M6 Rod end bearings
- Sealed to IP65 or IP68
- 2M PVC cable



Technical Specification

Product Code	IER
Stroke	±0.5mm to ±550mm
Input Voltage	9-24 VDC (dependent on conditioning unit)
Non-Linearity	±0.5% of full range, (higher specification can be achieved at extra cost)
Repeatability	Better than 0.1%
Resolution	Infinite (dependent on measuring instrument)
Frequency Response	3dB @ 180Hz
Vibration Resistance	20g up to 2kHz
Shock Resistance	1000g for 10 milliseconds
Insulation Resistance	Above 10MΩ at 500VDC (between wires and case)
Dielectric Strength	500V RMS for one minute (between wires and case)
Magnetic Shielding	Internal magnetic shielding
Construction Material	Stainless steel
Sealing	IP65

Option Description

G	Extension rod wiper
W	Waterproof IP68, with PU cable and stainless steel M6 rod end bearings
I	4-20mA Output (Datasheet SS0192)
U	0-5V Output (Datasheet SS0394)
U-10	0-10V Output (Datasheet SS0394)
D	DC Bipolar Output (Datasheet SS0393)
Y	Reverse output (e.g. 4mA fully in instead of default 20mA)
Z	Armoured hose
L	Increased linearity, $\pm 0.25\%$

Dimensions

