



FOR	SEPA	RATE TYPE LEVEL SWITCH		
MOUNT	ING	TOP & SIDE, SCREW		
ENCLOSURE		WEATHER PROOF (IP65)		
AMBIEN	NT TEMP.	−20 ~ +60 °C		
MAX. F	PRESSURE	10 kgf/cm²		
MAX.	TEMP.	150 °C		
			•	

CABLE CONNECTION SIZE   SHELL 14S
-----------------------------------

NO.	DESCRIPTION	MATERIAL	REMARK
1	WEIGHT	C.S	
2	BODY	C.S	
3	COVER	C.S	
4	PROCESS CONN.	304 SS	
5	SENSING ROD	316L SS	

PROCESS	CONN.	SIZE
PT 3/4"(M)		

TAG. NO.	QT <b>'</b> Y	REMARK
	2	

 $\frac{\text{NOTE}}{\text{1. GENERAL TOLERANCE }\pm 3\text{mm}} \quad \text{EXCEPT AS NOTED.}$ 

4						HITROL CO., LTD.	SCALE	UNIT	SHEET NO.
<u>\$</u>						HIROL CO., LID.	N.S	mm	
<u> </u>						TITLE	PROJECT		
Â						VIBRATION TYPE LEVEL SWITCH			
◬	JAN. 2018	1st ISSUE	D Y KIM	B S SUNG	Y H KIM	HTM-930	DRAWING NO.		
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY	111M 550	HTM930-A-01		

This drawing is the property of HITROL and shall not be copied, communicated, or given for third—party except with our written permission.