



ART. 33/2011NHHV2

Diaphragm pumps - entirely in aluminum

Diaphragm pump series 3/4" 340-AB in aluminum with membrane in NBR



FLUIDS

WASTE OIL | FRESH OIL | ANTIFREEZE | WINDSHIELD FLUID | WATER

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

WASTE OIL | FRESH OIL | ANTIFREEZE | WINDSHIELD FLUID | WATER

CERTIFICATIONS

ATEX (ZONE 1) | ATEX (ZONE 21)

Features	UM	Value
Flow rate	l/min	70
Ratio		1:1
Compatible fluids		water, mineral-vegetable oils, diesel fuel
Pump material		aluminum
Ball valve material		Hytrel®
Air inlet connection		G 3/8" (f)
Fluid inlet-outlet connection		G 3/4" (f) x G 3/4" (f)
Air working pressure	bar	2 ÷ 6
Max supply pressure	bar	8
Average air consumption	l/min	500
Noise level	dB	75
Fluid temperature	°C	-10 ÷ +90
Max solids diameter	mm	ø 1,5
Suitable for drums or tanks		modular
Suction-delivery ball valve with spring		ball valve with spring
Packing	N° - m³	1 - 0,015
Weight	kg	8
Dimensions (A-B-C)	cm	16 - 20 - 25,6
Suction tube length and ø	cm	-

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2018 All rights reserved to RAASM S.p.A.